

LBB 4540 Integrus

www.boschsecurity.com.cn



u
u
u 2 LCD
u

LBB 4560

Technical Specifications

-
- NiMH AA LBB 4550/10
-
-
-
-
- 200
- 75
- 1 45
- 2 LCD
-
- /
- LED
- 3.5 0.14
- AA
- LBB 4550/10

	4 mW/m ²
	± 50°
2.4 V	450 mVrms 32
	20 Hz 20 kHz
	32 2
	80 dB(A)
	1.8 3.6 V 2.4 V
2.4 V	15 mVrms 32
	< 1 mA
x x	155 x 45 x 30 6.1 x 1.8 x 1.2

	75	0.16
	125	0.27

LBB 4540/04 4
Integrus 4
LBB4540/04

LBB 4540/08 8
Integrus 8
LBB4540/08

LBB 4540/32 32
Integrus 32
LBB4540/32

LBB 4550/10 Integrus NiMH **10**
Integrus NiMH 10
LBB4550/10

LBB 4550/00 Integrus NiMH
LBB4550/00

LBB 4560/00 Integrus
LBB4560/00

LBB 4560/50 Integrus
LBB4650/50

: 333 : 200335 : +86 21 22181111 : +86 21 22182388 www.boschsecurity.com.cn	: 11 5 506-509 :+852 2635 2815 :+852 2648 7986 www.boschsecurity.com.cn
--	--