

LBB 451x/00 Integrus

www.boschsecurity.com.cn

u	LBB 4511/00	1300	4
u	LBB 4512/00	2600	4
u		(IRED)	

u
u

•

- HF 2 x BNC

1	LBB 451x/00 Integrus
1	
1	
2	

	100-240Vac 50-60Hz
LBB 4511	100W
LBB 4511	8W
LBB 4512	180W

-
-
- LED
-
-
-
-
-
- IRED
-
- 2 LED
- 2 LED
- LED LED
- LED LED
-

LBB 4512	10W	
IRED		
LBB 4511	260	
LBB 4512	480	
LBB 4511	12W/sr	
LBB 4512	24W/sr	
	± 22°	
HF	1 Vpp	10mVpp

	•	
	•	MIO 1/2
	•	
	•	(LBB 3414/00)
x x		
LBB 4511	200x500x175	
	7.9x19.7x6.9	
LBB 4512	300x500x175	
	11.0x19.7x6.9	
	0 15 30°	
/	0 15 30 45 60 75 90°	
LBB 4511	6.8	15
LBB 4511	7.6	17
LBB 4512	9.5	21
LBB 4512	10.3	23

LBB 4512/00-US Integrus (US)
 Integrus 2600
 27986
LBB4512/00-US

LBB 3414/00
 LBB 3414/00
LBB3414/00

INT-FCRAD
 1 INT-FCRAD
INT-FCRAD

LBB 4511/00 Integrus
 Integrus 1300
 13993
LBB4511/00

LBB 4512/00 Integrus
 Integrus 2600
 27986
LBB4512/00

LBB 4511/00-US Integrus (US)
 Integrus 1300
 13993
LBB4511/00-US

:
:
333 11 5
: 200335 506-509
: +86 21 22181111 :+852 2635 2815
: +86 21 22182388 :+852 2648 7986
www.boschsecurity.com.cn www.boschsecurity.com.cn