

**HU**

®

**SHURE**  
UA846Z2

GLX-D Frequency Manager

POWER

**SHURE**  
GLXD4R

rf gold  
5S  
auto  
A1 15.52 -20  
channel

**SHURE**  
GLXD4R

rf gold  
5S  
auto  
A2 12.39 -20  
channel

**SHURE**  
GLXD4R

rf gold  
5S  
auto  
A3 15.55 -20  
channel

**SHURE**  
GLXD4R

rf gold  
5S  
auto  
A4 09.20 -20  
channel

**SHURE**  
GLXD4R

rf gold  
5S  
auto  
A5 15.51 -20  
channel

**SHURE**  
GLXD4R

rf gold  
5S  
auto  
A6 11.43 -20  
channel

GLX-D® ADVANCED



- A C

# GLX-D ADVANCED



A

-

/

GLXD4R

2.4 GH



LED

LCD

XLR

1

GLXD4R

GLXD1  
GLXD2

SM58

30  
20  
16

60  
50



GLX-D A

GLX-D

1. GLX-D

GLXD4R

2.4 GH



2. GLX-D

( 11 )

9

A

GLX-D



A 05 - A

8 B

24 B 2.4GH



A505

PA805Z2-RSMA UA8-Z2



A

50

6 25 50 100

3.


GLX-D

4.

---

GLX-D

USB





GLX-D A

	<b>A</b>		<b>A 05 - A</b>
9 11	15 VDC	42 197 163 ( )	<2.1 (VSWR) 2050 2700 MH
30 (100 ) 60 (200 ) 20 (65 ) 50 (165 )	15 VDC ( 6)	907.2	(2.45 GH ) 8 B
GLX-D	18 C 63 C(0 F 145 F)		<b>3 dB</b> 100
20 H 20 H	45 483 192 ( )	14 18 VDC( )550 A	(2.45 GHz ) 89%
120 B A	1.63	18 42 B(1 B )	50
1 /A 4.0 2 3 4 /B 7.3	SMA	/ 30 B	(2.45 GHz ) 24 B
-88 B ( )	2400 2483.5 MH	50	SMA
0.2%( )	35 B( )		105 164 27.5 ( )
10 WE.I.R.P.( )	50		70
18 C(0 F) 57 C(135 F)	10 B	20 B	
29 C( 20 F) 74 C(165 F)	+15 B		
( ) WA302 SMA			
3) 2( 1/4	2400 2483.5 MH (OIP3)		
16	48 B ( )		
/	50		
	35 B( )		
	3 0 B		

		<b>6.35</b> <b>(1/4 )</b>
	100	100 (50 )
	+18 BV 12 BV	+12 BV
	1= 2= 3=	= = =

<b>1</b>			
90.4 64.5 22.9 ( )		(SM58) 252 51 ( )	10 WE.I.R.P.( ) 145 B SPL
3.7 V	(1 H 1% )+ 8.4 BV (7.5 V - )		
900	TA4M	(SM58 ) 267	
10 WE.I.R.P.( )	1 ( ) 2 +5V 3 4	3.7 V	
4 (TA4M)	( ) 4 )		



625 22  
info@shure.com.hk

618  
(II) 18 A  
info@shure.com.cn

1  
816