

HU

®

SHURE
UA846Z2

GLX-D Frequency Manager

POWER

SHURE
GLXD4R

SHURE GLXD4R control panel with digital display showing A1 15.52 -20 and a frequency slider.

SHURE
GLXD4R

SHURE GLXD4R control panel with digital display showing A2 12.39 -20 and a frequency slider.

SHURE
GLXD4R

SHURE GLXD4R control panel with digital display showing A3 15.55 -20 and a frequency slider. A hand is pointing at the slider.

SHURE
GLXD4R

SHURE GLXD4R control panel with digital display showing A4 09.20 -20 and a frequency slider.

SHURE
GLXD4R

SHURE GLXD4R control panel with digital display showing A5 15.51 -20 and a frequency slider. A hand is pointing at the slider.

SHURE
GLXD4R

SHURE GLXD4R control panel with digital display showing A6 11.43 -20 and a frequency slider.

GLX-D® ADVANCED



- A C

GLX-D ADVANCED



A -

/

GLXD4R

2.4 GH



LED

LCD

XLR ¼

1

GLXD4R

GLXD1

GLXD2

SM58

30

60

20

50

16



GLX-D A

GLX-D

1. GLX-D

GLXD4R

2.4 GH



2. GLX-D

(11)

9

A

GLX-D



A 05 - A

8 B



A505

PA805Z2-RSMA UA8-Z2



A

50

6 25 50 100

24 B 2.4GH


3.

GLX-D

4.

GLX-D

USB





GLX-D A

| | | | |
|---|--------------------------|-------------------|-----------------------------|
| | A | | A 05 - A |
| 9 11 | 15 VDC | 42 197 163 () | <2.1 (VSWR) 2050 2700 MH |
| 30 (100) 60 (200) 20 (65) 50 (165) | 15 VDC (6) | 907.2 | (2.45 GH) 8 B |
| GLX-D | 18 C 63 C(0 F 145 F) | | 3 dB 100 |
| 20 H 20 kH | 45 483 192 () | 14 18 VDC()550 A | (2.45 GHz) 89% |
| 120 B A | 1.63 | 18 42 B(1 B) | 50 |
| 1 /A 4.0 2 3 4 /B 7.3 | SMA | / 30 B | (2.45 GHz) 24 B |
| -88 B () | 2400 2483.5 MH | 50 | SMA |
| 0.2%() | 35 B() | 50 | 105 164 27.5 () |
| 10 W E.I.R.P.() | 50 | ½ | 70 |
| 18 C(0 F) 57 C(135 F) | 10 B | 20 B | |
| 29 C(20 F) 74 C(165 F) | +15 B | | |
| () WA302 SMA | | | |
| 3) 2(1/4 | 2400 2483.5 MH (OIP3) | | |
| 16 | 48 B () | | |
| / | 50 | | |
| | 35 B() | | |
| | 3 0 B | | |

| | | |
|--|-----------------|------------------------------|
| | | 6.35 (1/4) |
| | | |
| | 100 | 100 (50) |
| | +18 BV 12 BV | +12 BV |
| | 1= 2= 3= | = = = |

| | | | |
|-----------------------|----------------------------------|----------------|------------------|
| 1 | | | |
| 90.4 64.5 22.9 () | | (SM58) | 10 W E.I.R.P.() |
| 3.7 V | (1 kH 1%)+ 8.4 BV (7.5 V -) | 252 51 () | 145 B SPL |
| 900 k | TA4M | (SM58) 267 | |
| 10 W E.I.R.P.() | 1 () 2 +5V 3 4 | 3.7 V | |
| 4 (TA4M) | (4) | | |



625 22
info@shure.com.hk

618
(II) 18 A
info@shure.com.cn

1
816