

# SHURE®

LEGENDARY  
PERFORMANCE™

ULX-D™





## ULX-D™



ULX-D



15

12



Workbench™ 6

Dante™

Wireless

## ULX-D



ULX-D



ULX-D

(AES) 256



ULX-D

# ULX-D™

## ULXD4



## ULXD4D



## ULXD4Q



24- /48

20 20

120

60

72

8

8

23

63

A 256

6

A 600 A

A /

1/2

120

A 256

900

11

200

2 AA

11

100

58) 0 4.6.1659>-6 ( ) / 201 -0.018 0.018 1.148 0 6 >-12>-28654<0A9>-41<1 0 A>1





ULX-D™



1mW

- 8MHz 63 ULX-D
- 125 kHz
- 30 100



8MHz 63



Dante IP

- Dante ULX-D
- Dante
- ULXD4D ULXD4Q



ULX-D

- 
- 
- ULXD4D ULXD4Q

		470	932		
		>70			
		<2.9			
		-98	10 <sup>-5</sup>		
			100		
		20	-20		
			>120	A	
	@ +10		130		A
			<0.1%		
12	↻	@ +10			
			-18	(0 ↘ -50	(122 ↘)



		4	171	197	42		
		4		4	482	274	44
		4	0.9				
		4	3.36				
		4	3.45				
		4	15		@ 0.6 A		
		4	100 - 240	μA	50-60	0.26 A	
		4	100 - 240	μA	50-60	0.32 A	
		-18	+42		1		
		¼	6.35		+12		4
					+18		-12
		4			10/100		
		4		4		1	
		↻		↻			
		4					
		4		4			

		1	86	66	23		
		2	256	51			
		1	142				
		2	340				
	@ 10 mW	↻	900			11	
		2	AA			11	
		1	, 10	, 20			
		1					
		2					
		1	¼				
		2					